


TURKFLEX KONTRAT HALI TEKNİK ÖZELLİKLERİ / TURKFLEX CONTRACT CARPETS TECHNICAL SPECIFICATIONS

	CUT PILE SAXONY PA 6 - CONTRACT CARPETS				
	800 gr/m ² PA 6 SAXONY	1000 gr/m ² PA 6 SAXONY	1200 gr/m ² PA 6 SAXONY	1400 gr/m ² PA 6 SAXONY	1650 gr/m ² PA 6 SAXONY
ÜRETİM METODU (Production Process)	WALL TO WALL CHROMOJET PRINTED CUT PILE				
HAV MALZEMESİ (Pile Material)	100% Polyamide 6 (nylon)				
İPLİK CİNSİ (Yarn Description)	Twisted & Heatset Yarn				
İĞNE ARALIĞI (Gauge)	1 / 10 Inch CUT PILE				
HAV YÜKSEKLİĞİ / mm, tolerance ± 0,25 mm (Pile Height)	6,0 mm (± 0,25)	6,5 mm (± 0,25)	7,5 mm (± 0,25)	8,5 mm (± 0,25)	12,5 mm (± 0,25)
TOPLAM YÜKSEKLİK ACTIONBACK TABAN (Total Height with Actionback) / mm, tolerance ± 0,25 mm	7,5 mm with Actionback	8,0 mm with Actionback	9,0 mm with Actionback	10,0 mm with Actionback	14,0 mm with Actionback
TOPLAM YÜKSEKLİK 300 gr KEÇE TABAN (Total Height with Feltback) / mm, tolerance ± 0,25 mm	8,5 mm with Feltback	9,0 mm with Feltback	10,0 mm with Feltback	11,0 mm with Feltback	15,0 mm with Feltback
HAV AĞIRLIĞI - gr / m ² , tolerance ± %5 (Pile Weight)	800 gr/m ² (± %5)	1.000 gr/m ² (± %5)	1.200 gr/m ² (± %5)	1.400 gr/m ² (± %5)	1.650 gr/m ² (± %5)
TOPLAM AĞIRLIK ACTIONBACK TABAN (Total Weight with Actionback) / gr/m ² , tolerance ± %5	1.850 gr/m ² with Actionback	2.050 gr/m ² with Actionback	2.250 gr/m ² with Actionback	2.450 gr/m ² with Actionback	2.700 gr/m ² with Actionback
TOPLAM AĞIRLIK 300 gr KEÇE TABAN (Total Weight with Feltback) / gr/m ² , tolerance ± %5	2.050 gr/m ² with Feltback	2.250 gr/m ² with Feltback	2.450 gr/m ² with Feltback	2.650 gr/m ² with Feltback	2.900 gr/m ² with Feltback
DOKUMA SIKLIĞI - ilmek/10 cm, tolerance ± 1 (Stitches/10 cm)	45 / 10 cm	58 / 10 cm	58 / 10 cm	58 / 10 cm	52 / 10 cm
İLMEK ADEDİ - ilmek/m ² (Number Of Tufts - tufts/m ²)	178.200 tufts/m ²	229.680 tufts/m ²	229.680 tufts/m ²	229.680 tufts/m ²	205.920 tufts/m ²
BİRİNCİ TABAN (Primary Backing)	WOVEN POLYPROPYLENE (PP)				
İKİNCİ TABAN - ACTIONBACK ya da KEÇE TABAN (Secondary Backing - Actionback or Feltback)	ACTIONBACK or FELTBACK				
BİTMİŞ ÜRÜN ENİ / cm, tolerance + %1 (Finish Roll Width)	400,0 cm (+ %1)				
ALEV ALMAZLIK TESTİ (Flammability Test Results)	Geçer (Passes)				
CLASSIFICATION OF REACTION TO FIRE (EN 13501-1:2007)	C fl - S1	B fl - S1	B fl - S1	C fl - S1	C fl - S1
STATİK ELEKTRİKLENME (Electrostatic Properties)	< 2.0 kV - Geçer (Passes)				

TURKFLEX ÜRÜN SEÇİM KRİTERLERİ / TURKFLEX PRODUCT SELECTION CRITERIA

KULLANIM ALANLARI (Target Places)	CUT PILE SAXONY PA 6 - CONTRACT CARPETS				
	800 gr/m ² PA 6 SAXONY	1000 gr/m ² PA 6 SAXONY	1200 gr/m ² PA 6 SAXONY	1400 gr/m ² PA 6 SAXONY	1650 gr/m ² PA 6 SAXONY
CAMİLER (Mosque)	★	★★	★★	★★★	★★★★
OTEL ODALARI (Hotel Rooms)	★	★★★	★★★	★★★	★★★★
OTEL KORİDORLARI ve LOBİLER (Hotel Corridors & Lobbies)		★★	★★★	★★★	★★★★
MERDİVENLER (Stairs)		★	★★	★★★	★★★★
OFİSLER (Offices)	★	★★	★★★	★★★	★★★★
BAR, KAFE, YEMEK SALONLARI (Bar, Cafe & Restaurants)		★	★★	★★★	★★★★
KONFERANS ve BALO SALONLARI (Conference & Ball Rooms)	★	★★	★★	★★★	★★★★
TİYATRO ve SİNEMA SALONLARI (Theatres & Cinemas)	★	★★	★★★	★★★	★★★★
MAĞAZALAR (Shops)	★	★★	★★	★★★	★★★★

İŞARETLERİN ANLAMI / EXPLANATION OF SIGNS				
	★	★★	★★★	★★★★
Düşük Performans Low Performance	Standart Performans Standard Performance	Orta Performans Medium Performance	Yüksek Performans High Performance	Üstün Performans Excellence Performance

* Fabrikamız tarafından onaylanmak koşuluyla, yukarıda belirtilen teknik özellikler ve ürün konstrüksiyonlarında değişiklik yapılabilir.
Above given technical specifications can be changed according to customer demands as long as it has been confirmed by Turkflex.

* TURKFLEX; ürünlerine ait teknik özelliklerde önceden ilan etmeksizin değişiklik yapabilir. Bazı değerler hava koşulları, nem oranı ve benzeri nedenlerle farklılık gösterebilir.
Turkflex, has right to make changes on the technical specifications of this products without any prior notice.
Some values may vary differ because of the weather conditions, humidity or similar reasons.